

# UNITED

LABORATORIES

## United 101

# Moisture Barrier And Electrical Lubricant

**Non-Chlorinated • Non-Flammable  
Penetrates & Cleans • Frees Frozen Fittings  
Leaves Protecting, Non-Drying, Waterproof Film  
Dries Out Electrical Equipment  
39,000 Volt Dielectric Strength**

**DANGER**  
**CONTAINS GAS UNDER PRESSURE;**  
**MAY EXPLODE IF HEATED.**  
**KEEP OUT OF REACH OF CHILDREN.**  
**SEE OTHER CAUTIONS ON BACK PANEL.**

**NET WT. 10.25 oz. (291 g)**

*PRECAUCION AL USARIO: Si usted no puede leer Ingles,  
pregunte a alguien que le traduzca esta etiqueta para  
usted antes de uso.*

**Sold By:**  
**UNITED LABORATORIES, INC.**  
**320 37th Avenue • St. Charles, IL 60174**  
**1-800-323-2594 • www.unitedlabsinc.com**

**PENETRATES** through rust and scale to loosen parts which have been frozen by corrosion. **LUBRICATES** parts to ensure free and easy movement. **DEMOISTURIZES** and creates a waterproof film that dries out electrical equipment, inhibits corrosion and prevents electrical discharge. Electronic Cleaners do not contain more than 75% VOC. **PROTECTS** and creates a non-drying film that seals parts against atmospheric and mild chemical corrosion.

#### DIRECTIONS

**TO REMOVE CORROSION:** Spray liberally directly onto dirt and scale. Allow to penetrate. Remove loosened scale, then reapply to leave an anticorrosive coating.

**TO DISPLACE MOISTURE:** Spray electrical equipment until thoroughly saturated. Allow to penetrate before attempting to restart, then reapply to protect surface.

**TO LOOSEN FROZEN NUTS AND BOLTS:** Apply liberally to frozen nuts, bolts, hinges and sliding and rotating parts. Allow to penetrate into threads. Work parts back and forth, then reapply to leave a never-dry, protective lubricating film.

To ensure adequate protection, reapply periodically.

An SDS for this product is available through United's website, [www.unitedlabsinc.com](http://www.unitedlabsinc.com), providing 24 hour access. Please read the SDS carefully and follow all directions when using or handling this product.



419

**DANGER:** Contains gas under pressure; May explode if heated. May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child.



Keep away from heat, sparks, open flames, and hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Obtain special instructions before use. Do not handle until all precautions have been read and understood. Wear protective gloves, clothing and eye protection. **If exposed or concerned:** Get medical attention. **IF SWALLOWED:** Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



#### Additional First Aid Measures:

**IF ON SKIN:** Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**IF INHALED:** Move to fresh air. If breathing is difficult, administer oxygen. If not breathing, administer artificial respiration. Seek immediate medical attention.

**CONTAINS (CAS):** Mineral Oil (8042-47-5), Carbon Dioxide (124-38-9), Octamethylcyclotetrasiloxane (556-67-2), Petroleum naphtha (Confidential).

**⚠ WARNING:** This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**Caution:** Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**