

UNITED

LABORATORIES

Use on equipment throughout the year to provide a slick, non-stick coating that provides superior release action. **United 127** protects metal, fiberglass, painted and plastic finishes. Applying **Seasonal Equipment Wax** to these types of surfaces reduces drag and sticking of many materials to the surface. It also leaves surfaces water and rust resistant.

In Spring, Summer and Fall:

Treat lawn mower decks, blades, weed wackers, chippers, edgers and trimmers to lessen drag and increase efficiency. **Seasonal Equipment Wax** will keep damp grass and other clippings from sticking to treated surfaces, while protecting metal surfaces from the corrosive effects of fertilizer and other lawn care treatments.

In Winter:

Use **United 127** to treat snow plows, shovels, street signs and road signs to prevent ice and snow from sticking to their surfaces. **Seasonal Equipment Wax** increases plow efficiency and helps protect metal surfaces from the corrosive effects of the winter weather, salt and other treatments that are used to keep roadways, parking lots and walkways clear of snow and ice.

Directions:

Shake well before using. Spray surface (comes out as a fine mist) from about 12 – 14 inches away. Allow a moment for wax coating to set up, but before the surface dries buff it with a clean cloth. After use, invert the can and spray a short burst to clear valve.

DANGER: Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Contains No Chlorinated Solvents and No CFC's



HMIS® III CODE 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX Consult your supervisor	HEALTH	*3
	FLAMMABILITY	4
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	X

* = CHRONIC

United 127

Seasonal Equipment Wax

KEEP OUT OF REACH OF CHILDREN.
DANGER
EXTREMELY FLAMMABLE.
VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.
SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NET WT. 11 oz. (311 grams)

PRECAUCION AL USUARIO: Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Sold By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

DANGER: Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 49°C/120°F. Dispose of contents/container in accordance with local/regional/national/international regulations.



FIRST AID MEASURES:

IF IN EYES: Rinse with water. Get medical attention if irritation develops and persists.

IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF INHALED: Move to fresh air. Call a physician if symptoms develop or persist.

IF SWALLOWED: Immediately call a poison center/doctor: Do NOT induce vomiting.

IF EXPOSED OR CONCERNED: Get medical advice/attention.

CONTAINS (CAS No.): Butane (106-97-8), Naphtha (petroleum), hydrotreated light (64742-49-0), n-Hexane (110-54-3), Propane (74-98-6), Solvent Naphtha (Petroleum), Light Aliphatic (64742-89-8), Polydimethylsiloxane (63148-62-9), Cyclohexane (110-82-7), n-Heptane (142-82-5), Octamethylcyclotetrasiloxane (556-67-2) and Octane (111-65-9).

An SDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the SDS carefully and follow all directions when using or handling this product.

Made in USA

618