



# UNITED

LABORATORIES

**Contains NO Chlorinated Solvents  
(NO 1,1,1-Trichloroethane)  
EXCEEDS FED. SPEC MIL-A-907D**

**Anti-Seize Compound** prevents galling, seizing, pitting, fretting, corrosion and distortion of threaded, keyed, splined and press fitted assemblies. Protects at sustained temperatures of up to 2100°F. Highly resistant to moisture, weather, chemical fumes, salt spray and steam. Allows tighter, more vibration-proof seals using less torque while making disassembly easier.

**USE ON:** Industrial machinery, construction, farm, mining and earth moving equipment, textile and steel mill machinery, chemical processing equipment, marine hardware, vehicle fleets and assembly lines.

**DIRECTIONS:**

**SHAKE WELL BEFORE USING.**

Be sure surfaces are free of dirt, dust, oil or grease. Use can at temperatures above 65°F.

Hold can upright and spray 8 to 10 inches from surface. After each use invert can and use short burst to clear the valve.

**CONTAINS (CAS No.):** Butane (106-97-8), Distillates (Petroleum), Hydrotreated Light (64742-47-8), Propane (74-98-6), Triethanolamine (102-71-6), Acetone (67-64-1), Copper (7440-50-8), and Aluminum (7429-90-5).

Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin.

**⚠ WARNING:** This product can expose you to diethanolamine, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

An SDS for this product is available through United's website, [www.unitedlabsinc.com](http://www.unitedlabsinc.com), providing 24 hour access. Please read the SDS carefully and follow all directions when using or handling this product.

## United 188

# Anti-Seize Compound

**Extreme High Temperature  
Up to 2100°F. (1149°C.)**

## DANGER

**EXTREMELY FLAMMABLE.  
HARMFUL OR FATAL IF SWALLOWED.  
MAY CAUSE EYE IRRITATION.  
CONTENTS UNDER PRESSURE.  
SEE OTHER CAUTIONS ON BACK PANEL.**

**NET WT. 12 oz. (340 g)**

**PRECAUCION AL USARIO:**

*Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.*

**Sold By:  
UNITED LABORATORIES, INC.**

**320 37th Avenue • St. Charles, IL 60174  
1-800-323-2594 • [www.unitedlabsinc.com](http://www.unitedlabsinc.com)**

**DANGER:** Extremely flammable aerosol. May be fatal if swallowed and enters airways.



**Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling.**



**Wear eye/face protection. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Collect spillage. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.**

**ADDITIONAL FIRST AID MEASURES:**

**IF ON SKIN:** Immediately take off all contaminated clothing. Wash off with soap and water. Get medical attention if irritation develops or persists. For minor skin contact, avoid spreading material on unaffected skin.

**IF INHALED:** Move to fresh air. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Call a physician if symptoms develop or persist.

**IF SWALLOWED:** Have victim rinse mouth thoroughly with water. Call a physician or poison control center immediately. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If ingestion of a large amount does occur, seek medical attention.



Manufactured and Printed in U.S.A.

817