

# UNITED

LABORATORIES

- TOUGH.
- DURABLE.
- EXCEPTIONAL ADHESION—BONDS TO A WIDE RANGE.
- FAST CURING.
- EASY APPLICATION—REQUIRES NO SPECIAL TOOLS OR EQUIPMENT.

#### DIRECTIONS:

1. Twist off desired amount of product for immediate use.
2. Knead, immediately apply to the area to be repaired (no more than 2 minutes elapsed time.)
3. Surface can be smoothed by hand or cloth rubbing with tap water.
4. Allow to cure for one hour before further processing.

<b>HMIS® III CODE</b> 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE <b>PERSONAL PROTECTION INDEX</b> Glasses and Gloves	HEALTH	1
	FLAMMABILITY	1
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	B

NET CONTENTS: 2 OZ. (57 g)

## United 298W

# STIK-IT Wood Epoxy

KEEP OUT OF REACH OF CHILDREN.

## WARNING

READ ALL CAUTIONS BEFORE USING.  
HARMFUL IF SWALLOWED.

PRECAUCION AL USARIO: Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

UNITED LABORATORIES, INC.  
320 37th Avenue • St. Charles, IL 60174  
1-800-323-2594 • www.unitedlabsinc.com

#### WARNING:

Contains epoxy and amine resins. May cause irritation to sensitive skin. Wash hands thoroughly with soap and water after use. Avoid contact with eyes—can cause irritation. In case of eye contact, flood with cool water for 15 minutes and consult a physician.

#### EMERGENCY AND FIRST AID PROCEDURES:

**EYES:** Flush with plenty of water for at least 15 minutes while holding eye lids open. If irritation persists, call a physician or poison control center.

**SKIN:** Wash with soap and water. If irritation persists, call a physician or poison control center.

**INHALATION:** Remove to fresh air. Apply CPR if needed. If irritation persists, call a physician or poison control center.

**IF SWALLOWED:** Call a physician or poison control center immediately.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

Printed in U.S.A.

605

#### FEATURES:

- Instant repairs on equipment and machinery.
- Highly portable: any worker can carry a tube for emergencies.
- Hardens quickly. No standing around waiting for product to activate.
- Rust proof.

#### BENEFITS:

- Field repairs done quickly—less down time and fewer expensive maintenance calls.
- No need to call out expensive specialists with bulky equipment.

#### PERFORMANCE DATA\*:

WORKING LIFE (minutes) .....	15
SHELF STABILITY (months @ 75°F, minimum) .....	24
NON-VOLATILE CONTENT (%) .....	100
SHRINKAGE (%) .....	<1
DENSITY .....	7 lb/gal (0.8 gm/cm <sup>3</sup> )
HARDNESS, SHORE D (full cure, 24 hrs.) .....	70-80
LAP SHEAR TENSILE (On Cold Rolled Steel p.s.i.) .....	500
COMPRESSIVE STRENGTH (p.s.i.) .....	12,000
ELECTRICAL RESISTANCE (megohms) .....	30,000
DIELECTRIC STRENGTH (volts/mil) .....	300
UPPER TEMPERATURE LIMIT Continuous (°F) .....	250
Intermittent (°F) .....	300
CHEMICAL RESISTANCE: Resistance to hydrocarbons, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.	

\* Not to be used for specification purposes.