



UNITED

L A B O R A T O R I E S

SHAKE WELL BEFORE USING

NOMIX is a heavy-duty polyurea polymer filler for repairing cracks, gouges, holes and surface delamination in concrete. Ideal for use in warehouses, garages, shops or anywhere cracks in concrete floors are a problem.

NOMIX is formulated to minimize downtime:

- Convenient dual cartridge and static mixer eliminates mixing.
- Works at temperatures as low as -20° Fahrenheit.
- Fast setting. **NOMIX** will withstand heavy traffic within 30 minutes.
- Low odor.
- Becomes hard and rubber-like when cured. Won't become brittle with aging.

DIRECTIONS FOR USE:

Surface should be free of dirt, debris, frost or moisture. Surface preparation is important to assure proper adhesion.

United 541 NOMIX is a two component material that needs to be applied with a special two part dispensing gun—the A541 NOMIX Dual Feed Dispenser. It mixes the proper amount of the two components during application.

Using the A541 NOMIX Dual Feed Dispenser with Static Mixer, fill the cracks being repaired. Cured filler can be shaved to level with a razor. For wider applications, fill crack as flush as possible to the surface. Using a belt-sander with 40, 60, or 80 grit paper, level the **NOMIX** with the floor.

APPLICATIONS BELOW FREEZING: When applying at temperatures below 32°F (0°C) pre-warm cartridges to 90°F (33°C). This can be done using heated water or heated box.

FOR INDUSTRIAL USE ONLY

Keep Away From Children and Pets

Store in a dry place. Protect from freezing. Cartridge should be stored or conditioned to 65°F - 75°F prior to use for best results. Do not expose to direct sunlight as discoloration may occur.

United 541

NOMIX

Concrete Repair

**KEEP OUT OF REACH OF CHILDREN.
SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.**

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

For Chemical Emergency - Spill, Leak, Fire, Exposure, or Accident, Call:

INFOTRAC (800) 535-5053 24-Hour Contact

United 541 NOMIX Part A Warning

May cause an allergic skin reaction. Avoid breathing mist, vapors, or spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse. Dispose of contents/container in accordance with local, regional, national, international regulations. There are no other hazards not otherwise classified that have been identified.



United 541 NOMIX Part B Danger

Harmful if inhaled Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection In case of inadequate ventilation wear respiratory protection. **IF ON SKIN:** Wash with plenty of soap and water. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash it before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. There are no other hazards not otherwise classified that have been identified.



READ PRODUCT DATA / SDS BEFORE USE

In Case of Fire: Use water fog, foam, dry chemical or carbon dioxide. Exposed firefighters must wear NIOSH-approved positive pressure self-contained breathing apparatus with full-face mask and full protective clothing.

An SDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the SDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.