



UNITED

LABORATORIES

United 317

- Prevents costly pipe bursts
- Protection to -40°F
- Compatible with United 320 and 323

CAUTION:

To prevent freeze ups in recirculating cooling water systems: This product diluted with 2 parts of water will normally protect to 0°F.

For Protection To:	Add This Much Product for Every 100 Gallons of System Capacity:
25°F	12 gal
20°F	17 gal
10°F	25 gal
0°F	33 gal
-10°F	39 gal
-20°F	44 gal
-30°F	49 gal
-40°F	53 gal

For optimum control of system corrosion as well as the best freeze protection, use 1 gallon of United 320 or 323 for every 100 gallons of water/antifreeze mixture.

Cooling Tower Anti-Freeze

KEEP OUT OF REACH OF CHILDREN.

CAUTION

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
 320 37th Avenue • St. Charles, IL 60174
 1-800-323-2594 • www.unitedlabsinc.com

CAUTION:

Contains Propylene Glycol (CAS# 57-55-6). Avoid contact with eyes.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with plenty of water and call a physician or poison center.

SKIN: Wash with soap and water. If irritation persists, call a physician or poison control center.

INHALATION: Remove to fresh air. If irritation persists, call a physician or poison center.

IF SWALLOWED: Low in toxicity. Induce vomiting if large amounts are ingested. Call a physician or poison center immediately.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Glasses and Gloves	HEALTH	0
	FLAMMABILITY	1
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	B