

UNITED

LABORATORIES

United 496 NIGHTSHIFT Automatic Concrete Cleaner and Oil Stain Remover easily removes embedded oil-based stains from concrete and masonry without scrubbing.

Removes even the toughest stains, including:

- Oil • Grease • Anti-Freeze • Hydraulic Fluid
- Brake Fluid • Tar • Cosmolene
- Cooking Oils • Other Oil-Based Stains

Effective for use on concrete, brick and cinderblocks on...

- Driveways • Factory floors • Parking lots
- Parking garages • Garage floors • Sidewalks
- Shop floors • Loading docks • Porticos

DIRECTIONS:

Test in an inconspicuous area first and examine for discoloration. Please note this product is not for use on asphalt. For best results, use **United 496 NIGHTSHIFT Automatic Concrete Cleaner and Oil Stain Remover** when temperatures are above 55°F (13°C). This product is combustible. Use in areas with maximum ventilation and do not apply to hot surfaces in direct sunlight.

The solvents in this product may attack plastics. This product contains alkalies and surfactants that may discolor certain metals on sprayer parts. Test for incompatibility.

1. Shake or mix product well before using.
2. Remove any pooled or excess material using United 215 SURROUND Oil And Spill Encapsulate. Using disposable rags or paper towels try to blot away as much of the remaining stain as possible.
3. Generously pour **United 496 NIGHTSHIFT Automatic Concrete Cleaner and Oil Stain Remover** over stain to be treated. Make sure stain area is completely covered. For very heavy oil stains apply **United 496 NIGHTSHIFT**, agitate for 1 minute with a firm bristled brush, and then reapply **United 496 NIGHTSHIFT** to area.
4. Allow product to sit on stain for 15 to 24 hours. It must dry thoroughly to form a hardened, powdery material.
5. Using a hose or bucket and brush, rinse away the dried powder and stain. For best results, rinse for at least 30 seconds with a powerful stream.

United 496

NIGHTSHIFT Automatic Concrete Cleaner and Oil Stain Remover

**KEEP OUT OF REACH OF CHILDREN.
CAUTION
SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS.**

PRECAUCION AL USUARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

**Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com**

DIRECTIONS: (continued)

6. Allow concrete to dry for several hours. The stain should be gone.
7. Especially stubborn stains may require retreatment with **United 496 NIGHTSHIFT Automatic Concrete Cleaner and Oil Stain Remover**. Repeat the above procedure (steps 1 to 6).
8. In areas with storm sewer regulations the white powder can be wiped away with a disposable paper towel or rag. Then, hose the stain away for around 30 seconds using the strongest stream of water possible.
9. After using this product with a sprayer, be sure to rinse the hoses of the sprayer with water. Dried product will clog the sprayer hose.

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Immediately flush with plenty of water for at least 15 minutes while holding eyelids open. Get prompt medical attention.

SKIN: Wash with soap and plenty of water. Remove contaminated clothing. If irritation persists, call a physician or poison control center.

INHALATION: Remove to fresh air. If symptoms develop, seek immediate medical attention. If not breathing, give artificial respiration.

INGESTION: DO NOT induce vomiting. Get medical attention immediately. If vomiting occurs, have victim lean forward to reduce risk of aspiration.

An MSDS for this product is available through United's website, www.unitedlabsinc.com, for 24-hour access. Please read the MSDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

HMIS® III CODE: 0=MINIMAL 1=SLIGHT 2=MODERATE 3=SERIOUS 4=SEVERE PERSONAL PROTECTION INDEX: Glasses and Gloves	HEALTH	2
	FLAMMABILITY	2
	PHYSICAL HAZARD	0
	PERSONAL PROTECTION	B