



UNITED

LABORATORIES

- **United 573 DUST DOWN PLUS** may be used for dust control of unpaved roads and parking lots.
- **United 573 DUST DOWN PLUS** attracts moisture from the air, keeping the road damp even under hot, dry conditions.
- Proprietary Soil penetrant formula conditions the surface tension and boosts the dust control performance providing greater uniform coverage and maximum penetration.
- Reduces deteriorating road from dust.
- With consistent application year after year base stability improves.
- Blading frequency of roads is extended.
- Airborne particulate matter is reduced improving air quality.
- Using **United 573 DUST DOWN PLUS** decreases aggregate replacement cost.
- Effective and safe for the environment.

DIRECTIONS:

Before applying **United 573 DUST DOWN PLUS** perform some basic road maintenance. Surface must have the right contour, enough gravel and fines to stabilize the roadbed. Water road surface prior to blading, unless rain has fallen within two days. Remove ruts, potholes, washboards and mix in loose aggregate 3/4 inch to 1 inch well graded and shape road for good drainage.

Wet surface prior to spraying **DUST DOWN PLUS** on the roadbed. Application rates of 38 oz./yd² to 50 oz./yd² (2117 gal./lane-mile to 2744 gal./lane-mile) of **United 573 DUST DOWN PLUS** are recommended.

Coverage range for larger areas: 41 - 50 sq. feet/gallon.

Product longevity will vary with climate, soil type, and degree of compaction of the surface as well as traffic weight and frequency. A minimum of 3 to 6 months is common in some cases. When treated for maximum performance it lasts 3 plus years.

The hygroscopic and deliquescent nature of **United 573 DUST DOWN PLUS** keeps the treated surface moist and inhibits the creation of dust over a wide range of temperatures and humidity levels.

United 573

DUST DOWN PLUS Mineralized Dust Encapsulation

WARNING

KEEP OUT OF REACH OF CHILDREN.
See other cautions on back/side panel.

PRECAUCION AL USARIO:

Si usted no puede leer Ingles, pregunte a alguien que le traduzca esta etiqueta para usted antes de uso.

Manufactured and Sold Exclusively By:
UNITED LABORATORIES, INC.
320 37th Avenue • St. Charles, IL 60174
1-800-323-2594 • www.unitedlabsinc.com

WARNING: Causes serious eye irritation. May be harmful if swallowed.



Wash face, hands and any exposed skin thoroughly after handling. Wear eye/face protection. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

ADDITIONAL FIRST AID MEASURES:

IF ON SKIN: Flush area with water while removing contaminated clothing. Do not reuse clothing or shoes until cleaned. If irritation persists, get medical attention. Do not apply oils or ointments unless ordered to by a physician.

IF INHALED: Move person to fresh air. If person is not breathing, give artificial respiration preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

IF SWALLOWED: Drink large amounts of water to dilute. Do not induce vomiting. Call a physician immediately. Never induce vomiting or give anything by mouth to an unconscious person.

An SDS for this product is available through United's website, www.unitedlabsinc.com, providing 24 hour access. Please read the SDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

FOR INDUSTRIAL USE ONLY.