



LABORATORIES

Issue Date 11-Apr-2015

Revision Date 24-July-2015

Version 1

# Safety Data Sheet

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

**Product Name** United 154 HIGH-COAT Gloss Black

### Other means of identification

**SDS#** UNITED-154GB

### Recommended use of the chemical

#### And restrictions on use

**Recommended use** Industrial Strength Spray Paint-Gloss Black  
**Uses Advised Against** For industrial and institutional use only.

### Details of the supplier of the safety data sheet

#### **Company Name**

United Laboratories, Inc.  
320 37th Avenue  
St. Charles, IL 60174  
www.unitedlabsinc.com  
www.unitedlabsinc.ca

### Emergency telephone number

**Emergency Telephone** 800-323-2594 (to reorder)  
INFOTRAC 1-800-535-5053 (North America)  
1-352-323-3500 (International)

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable Aerosols	Category 1
Pressurized Gas	
Eye Irritation	Category 2A
Carcinogenicity	Category 2
STOT – Single Exposure	Category 3

### Label elements

#### Emergency Overview

## Danger

#### **Hazard statements**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness.

**Appearance** Gloss Black**Physical state** Aerosol**Odor** Aromatic**Prevention**

Read label before use. If medical advice is needed, have product container or label at hand. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Wash hands thoroughly after handling. Use only outdoors or in a well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Keep out of reach of children.

**Response**

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

**Storage**

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in well-ventilated area. Keep container tightly closed.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

Not classified.

**Environmental hazards**

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	22.56%	*
Propane	74-98-6	15.75%	*
n-Butane	106-97-8	9.25%	*
Barium Sulfate, Natural	7727-43-7	8.51%	
Methyl Isobutyl Ketone	108-10-1	5.47%	*
Glycol Ether EP	2807-30-6	5.45%	*
Methyl Propyl Ketone	107-87-9	3.06%	*
Xylene (Mix)	1330-20-7	2.69%	*
PM Acetate	108-65-6	1.87%	*
Isobutyl Acetate	110-19-0	1.41%	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**First aid measures****Skin Contact**

Remove contaminated clothing. Wash exposed area with soap and water.

**Eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**Inhalation** Supply fresh air; consult doctor in case of complaints.

**Ingestion** Rinse mouth with water. Do not induce vomiting.

**Most important symptoms and effects, both acute and delayed**

May cause dizziness.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Extinguishing powder or water spray. CO2. Fight larger fires with water spray.

**Unsuitable extinguishing media** None known.

**Protective equipment and precautions for firefighters**

As is any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**Specific Methods**

Use water spray to fight larger fires. Ventilate area.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Keep unnecessary personnel away. Wear appropriate protective equipment. Use respiratory protective device against the effects of fumes/dust/aerosol. For personal protection, see Section 8 of this SDS.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage into sewer systems or ground water. Eliminate all ignition sources (no smoking, flares, sparks or flames).

**Methods for cleaning up** Absorb liquid components with liquid-binding material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Keep away from heat, sparks, flame and other sources of ignition. Use in well ventilated areas. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store locked up. Do not handle or store near flame, heat and sources of ignition. Avoid exposure to direct sunlight, exceeding 50°C/122°F. Do not warehouse in subfreezing conditions.

**Incompatible materials** None known.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines** No Exposure limits noted for ingredient(s).

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	TWA: 500 ppm	PEL: 2400 mg/m <sup>3</sup> PEL: 1000 ppm	TWA: 590 mg/m <sup>3</sup> TWA: 250 ppm
Propane 74-98-6	TWA: 1000 ppm	PEL: 1800 mg/m <sup>3</sup> PEL: 1000 ppm	TWA: 1800 mg/m <sup>3</sup> TWA: 1000 ppm
n-Butane 106-97-8	TWA: 2370 mg/m <sup>3</sup> TWA: 1000 ppm	-	TWA: 1900 mg/m <sup>3</sup> TWA: 800 ppm
Methyl Isobutyl Ketone 108-10-1	TWA: 307 mg/m <sup>3</sup> TWA: 75 ppm TWA: 82 mg/m <sup>3</sup> TWA: 20 ppm	PEL: 410 mg/m <sup>3</sup> PEL: 100 ppm	TWA: 300 mg/m <sup>3</sup> TWA: 75 ppm TWA: 205 mg/m <sup>3</sup> TWA: 50 ppm
Barium Sulfate, Natural 7727-43-7	TWA: 5* mg/m <sup>3</sup> *inhalable fraction; E	PEL: 15* 5** mg/m <sup>3</sup> *total dust respirable fraction	TWA: 10*5** mg/m <sup>3</sup> *total dust Respirable fraction
Xylene 1330-20-7	TWA: 651 mg/m <sup>3</sup> TWA: 150 ppm TWA: 434 mg/m <sup>3</sup> TWA: 100 ppm	PEL: 435 mg/m <sup>3</sup> PEL: 100 ppm	TWA: 655 mg/m <sup>3</sup> TWA: 150 ppm TWA: 435 mg/m <sup>3</sup> TWA: 100 ppm
Methyl Propyl Ketone 107-87-9	TWA: 529 mg/m <sup>3</sup> TWA: 150 ppm	PEL: 700 mg/m <sup>3</sup> PEL: 200 ppm	TWA: 530 mg/m <sup>3</sup> TWA 150 ppm
Isobutyl Acetate 110-19-0	TWA: 713 mg/m <sup>3</sup> TWA: 150 ppm	PEL 700 mg/m <sup>3</sup> PEL: 150 ppm	TWA: 700 mg/m <sup>3</sup> TWA: 150 ppm
PM Acetate 108-65-6			

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Biological limit values** Acetone (67-64-1) - 50 mg/L – Urine / Methyl Isobutyl Ketone (108-10-1) – 1mg/L – Urine  
Xylene (1330-20-7) – 1.5 g/g creatinine – Urine.

**Workplace Environmental Exposure Limits** PM Acetate (108-65-6) 50 ppm, long-term value.

**Individual protection measures, such as personal protective equipment**

- Eye/face protection** Tightly sealed goggles.
- Skin and body protection** Wear protective gloves. The glove material must be impermeable and resistant to the substance.
- Respiratory protection** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**General Hygiene** Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

**Physical state** Aerosol  
**Appearance** Spray  
**Color** Gloss Black  
**Odor** Aromatic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No Information available.	

<b>Specific Gravity</b>	0.77-0.85 (H2O=1)
<b>Viscosity</b>	No Information available.
<b>Melting point/boiling/freezing point</b>	-44° C (-47°F)
<b>Flash point</b>	-19 °C (-2°F)
<b>Vapor pressure</b>	No information available.
<b>Vapor density</b>	No Information available
<b>Flammability (solid, gas)</b>	Extremely flammable.
<b>Upper</b>	10.9 vol.%
<b>Lower</b>	1.7 vol.%
<b>Danger of Explosion</b>	In use, may form flammable/explosive vapor-air mixture.
<b>Auto-Ignition</b>	Is not self-igniting.
<b>VOC Content</b>	488.9 g/l/ 4.08lb/gal.
<b>VOC Content (less exempt solvents)</b>	46.2%
<b>MIR Value</b>	1.11
<b>Relative density</b>	Between 0.77 and 0.85 (water equals 1.00)
<b>Vapor density</b>	No information available.
<b>Solubility</b>	No information available.
<b>Solids content</b>	30.9%

## 10. STABILITY AND REACTIVITY

### Reactivity

This product is stable and non-reactive under normal conditions of use, storage and transport.

### Chemical stability

Material is stable at normal conditions.

### Possibility of Hazardous Reactions

No dangerous reactions known.

### Conditions to avoid

Do not allow can to exceed 120° F. Do not warehouse in subfreezing temperatures.

### Hazardous Decomposition Products

No hazardous decomposition products are known.

### Incompatible materials

No information available.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	May be fatal if swallowed and enters airways.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Skin Contact</b>	No irritation effect.
<b>Ingestion</b>	Exposure by ingestion is unlikely since an aerosol, but if ingested may be harmful or fatal.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	No information available.

### Information on toxicological effects

**Acute toxicity** No information available.

Chemical Name	Dermal LD50	Oral LD50	Inhalation LC50/LD50
n-Butane 106-97-8	-	-	658 mg/l, 4 hours (Rat)
Methyl Isobutyl Ketone 108-10-1	16000 mg/kg (Rabbit)	2100 mg/kg (Rat)	8.3-16.6 mg/l, 4 hours (Rat)
Isobutyl Acetate 110-19-0	-	4763 mg/kg (Rat)	-
Xylene 1330-20-7	2000 mg/kg (Rabbit)	8700 mg/kg (Rat)	6350 mg/l, 4 hours (Rat)
PM Acetate 108-65-6	-	8500 mg/kg (Rat)	35.7 mg/l, 4 hours (Rat)

\*Estimates for product may be based on additional component data not shown.

**Skin/Eye irritation** No irritant to skin. Irritating effect for eyes.  
**Sensitization** This product does not have any sensitizing effects.  
**Germ cell mutagenicity** No information available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.  
**Carcinogenicity** This product is considered to be a carcinogen by IARC, ACGIH, NTP or OSHA. IARC - Methyl Isobutyl ketone (108-10-1) – Xylene-mix (1330-20-7)  
**STOT - single exposure** No Information available.  
**STOT - repeated exposure** No Information available.  
**Target organ effects** No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**  
 Hazardous for water, do not empty into drains.

**Persistence and degradability**  
 This product is degradable after prolonged exposure to natural weathering processes

**Bioaccumulation**  
 No Information available.

**Mobility in Soil**  
 No information available.

**Other adverse effects** No other adverse environmental effects.

**13. DISPOSAL CONSIDERATIONS**

**Disposal of wastes** Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate or crush. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Completely empty cans should be recycled.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**14. TRANSPORT INFORMATION**

This product meets the exception requirements of Section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the “Consumer Commodity-ORM-D” marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/2020 and may be used now in place of the “Consumer Commodity ORM-D” marking and both may be displayed concurrently.

**DOT**

UN/ID No. UN1950  
 Proper shipping name Aerosols, flammable  
 Transport hazard class(es) 2.1

**IATA**

UN/ID No. UN1950  
 UN proper shipping name Aerosols, flammable  
 Transport hazard class(es) 2.1

**IMDG**

UN/ID No. UN1950  
 Proper shipping name Aerosols, flammable  
 Transport hazard (class)es 2.1  
 Marine Pollutant No  
 Special precautions for user Warning: Gases  
 EMS Number F-D,S-U  
 Limited quantities (LQ) 1L

**15. REGULATORY INFORMATION**

**International Inventories**

**Country(s) or Region**

Canada Yes\*  
 United States Yes\*

\*Yes indicates this product complies with the inventory requirements administered by the governing country(s).

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations**

**SARA 313 (Specific toxic chemical listings):** Methyl Isobutyl Ketone (108-10-1), Barium Sulfate, natural (7727-43-7), Xylene – Mix (1330-20-7)

**Superfund Amendments and Reauthorization Act of 1986**

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	Yes

**SARA 355 Extremely Hazardous Substance**

None known.

**US State Regulations**

**Consumer Product Safety Commission**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**Canadian Environmental Protection Act-EPA**

Acetone (67-64-1), Barium Sulfate, natural (7727-43-7), Methyl Isobutyl Ketone (108-10-1), Xylene-mix (1330-20-7), Isobutyl Acetate (110-19-0).

**California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Carbon black (1333-86-4), Methyl Isobutyl Ketone (108-10-1), Ethyl Benzene (100-41-4).

**16. OTHER INFORMATION**

<u>NFPA</u>	Health hazards -	Flammability -	Reactivity -	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 1	Flammability 4	Reactivity 3	Personal protection X

Issue Date 11-Apr-2015  
Revision Date 24-July-2015  
Revision Note

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**



**1. PRODUCT AND COMPANY IDENTIFICATION****Product identifier****Product Name** United 154 HIGH-COAT Gloss White**Other means of identification****SDS#** UNITED-154GW**Recommended use of the chemical****And restrictions on use****Recommended use** Industrial Strength Spray Paint-Gloss White  
**Uses Advised Against** For industrial and institutional use only.**Details of the supplier of the safety data sheet****Company Name**United Laboratories, Inc.  
320 37th Avenue  
St. Charles, IL 60174  
www.unitedlabsinc.com  
www.unitedlabsinc.ca**Emergency telephone number****Emergency Telephone** 800-323-2594 (to reorder)  
INFOTRAC 1-800-535-5053 (North America)  
1-352-323-3500 (International)**2. HAZARDS IDENTIFICATION****Classification****OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable Aerosols	Category 1
Pressurized Gas	
Eye Irritation	Category 2A
Carcinogenicity	Category 2
STOT – Single Exposure	Category 3

**Label elements****Emergency Overview****Danger****Hazard statements**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness.



**Appearance** Gloss White Liquid

**Physical state** Aerosol

**Odor** Aromatic

**Prevention**

Read label before use. If medical advice is needed, have product container or label at hand. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Wash hands thoroughly after handling. Keep out of reach of children. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray.

**Response**

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

**Storage**

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in well-ventilated area. Keep container tightly closed.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

Not classified.

**Environmental hazards**

None known.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	17.81%	*
Propane	74-98-6	15.74%	*
Titanium dioxide	13463-67-7	11.31%	*
n-Butane	106-97-8	9.24%	*
Methyl Isobutyl Ketone	108-10-1	5.65%	*
Barium Sulfate, Natural	7727-43-7	5.01%	*
Glycol Ether EP	2807-30-6	4.81%	*
Isobutyl Acetate	110-19-0	4.57%	*
Methyl Propyl Ketone	107-87-9	2.94%	*
Xylene (Mix)	1330-20-7	2.43%	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**First aid measures**

**Skin Contact**

Remove contaminated clothing. Wash exposed area with soap and water.

**Eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**Inhalation** Supply fresh air; consult doctor in case of complaints.

**Ingestion** Rinse mouth with water. Do not induce vomiting.

**Most important symptoms and effects, both acute and delayed**

May cause dizziness.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Extinguishing powder or water spray. CO2.

**Unsuitable extinguishing media** None known.

**Specific hazards arising from the chemical**

Can form explosive gas-air mixtures.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**Specific Methods**

Use water spray to fight larger fires. Ventilate area.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions**

Keep unnecessary personnel away. Wear appropriate protective equipment. Use respiratory protective device against the effects of fumes/dust/aerosol. For personal protection, see Section 8 of this SDS.

**Environmental precautions**

**Environmental precautions**

Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

**Methods and material for containment and cleaning up**

**Methods for containment**

Prevent further leakage or spillage into sewer systems or ground water. Eliminate all ignition sources (no smoking, flares, sparks or flames).

**Methods for cleaning up**

Prevent entry into waterways, sewers. Clean contaminated surface thoroughly to remove residual contamination. Absorb liquid components with liquid-binding material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling**

Keep away from heat, sparks, flame and other sources of ignition. Use in well ventilated areas. Do not spray on a naked flame or any incandescent material. Observe good industrial hygiene practices. Keep away from children.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store locked up. Do not handle or store near flame, heat and sources of ignition. Avoid exposure to direct sunlight, exceeding 50°C/122°F. Do not warehouse in subfreezing conditions.

**Incompatible materials** None known.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines** No Exposure limits noted for ingredient(s).

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	TWA: 500 ppm	PEL: 2400 mg/m <sup>3</sup> PEL: 1000 ppm	TWA: 590 mg/m <sup>3</sup> TWA: 250 ppm
Propane 74-98-6	TWA: 1000 ppm	PEL: 1800 mg/m <sup>3</sup> PEL: 1000 ppm	TWA: 1800 mg/m <sup>3</sup> TWA: 1000 ppm
n-Butane 106-97-8	TWA: 2370 mg/m <sup>3</sup> TWA: 1000 ppm	-	TWA: 1900 mg/m <sup>3</sup> TWA: 800 ppm
Methyl Isobutyl Ketone 108-10-1	TWA: 307 mg/m <sup>3</sup> TWA: 75 ppm TWA: 82 mg/m <sup>3</sup> TWA: 20 ppm	PEL: 410 mg/m <sup>3</sup> PEL: 100 ppm	TWA: 300 mg/m <sup>3</sup> TWA: 75 ppm TWA: 205 mg/m <sup>3</sup> TWA: 50 ppm
Barium Sulfate, Natural 7727-43-7	TWA: 5* mg/m <sup>3</sup> *inhalable fraction; E	PEL: 15* 5** mg/m <sup>3</sup> *total dust respirable fraction	TWA: 10*5** mg/m <sup>3</sup> *total dust Respirable fraction
Xylene 1330-20-7	TWA: 651 mg/m <sup>3</sup> TWA: 150 ppm TWA: 434 mg/m <sup>3</sup> TWA: 100 ppm	PEL: 435 mg/m <sup>3</sup> PEL: 100 ppm	TWA: 655 mg/m <sup>3</sup> TWA: 150 ppm TWA: 435 mg/m <sup>3</sup> TWA: 100 ppm
Methyl Propyl Ketone 107-87-9	TWA: 529 mg/m <sup>3</sup> TWA: 150 ppm	PEL: 700 mg/m <sup>3</sup> PEL: 200 ppm	TWA: 530 mg/m <sup>3</sup> TWA 150 ppm
Isobutyl Acetate 110-19-0	TWA: 713 mg/m <sup>3</sup> TWA: 150 ppm	PEL 700 mg/m <sup>3</sup> PEL: 150 ppm	TWA: 700 mg/m <sup>3</sup> TWA: 150 ppm

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Biological limit values** Acetone (67-64-1) - 50 mg/L – Urine / Methyl Isobutyl Ketone (108-10-1) – 1mg/L – Urine  
Xylene (1330-20-7) – 1.5 g/g creatinine - Urine

**Appropriate engineering controls**

**Engineering Controls** Local exhaust is recommended.

**Individual protection measures, such as personal protective equipment**

- Eye/face protection** Tightly sealed goggles.
- Skin and body protection** Wear protective gloves. The glove material must be impermeable and resistant to the substance.
- Respiratory protection** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**General Hygiene** Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	Aerosol
<b>Appearance</b>	Spray
<b>Color</b>	Gloss White
<b>Odor</b>	Aromatic.

<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks • Method</u></b>
pH	No Information available.	
Specific Gravity	0.77-0.85 (H2O=1)	
Viscosity	No Information available.	
Melting point/freezing point	-44° C (-47°F)	
Flash point	-19 °C (-2°F)	
Vapor pressure	No information available.	
Vapor density	No Information available	
Flammability (solid, gas)	Extremely flammable.	
Upper	10.9 vol.%	
Lower	1.7 vol.%	
Auto-Ignition	Is not self-igniting	
VOC Content	495.7 g/l/ 4.14lb/gl	
VOC Content (less exempt solvents)	46.0%	
MIR Value	1.05	
Relative density	Between 0.77 and 0.85 (water equals 1.00)	
Vapor density	No information available.	
Solubility	Insoluble	
Solids content	35.4%	

**10. STABILITY AND REACTIVITY**

**Reactivity**

This product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability**

Material is stable at normal conditions.

**Possibility of Hazardous Reactions**

No dangerous reactions known.

**Conditions to avoid**

Do not allow can to exceed 120° F. Do not warehouse in subfreezing temperatures.

**Hazardous Decomposition Products**

No hazardous decomposition products are known.

**Incompatible materials**

No information available.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information**

<b>Inhalation</b>	May be fatal if swallowed and enters airways.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Skin Contact</b>	No irritating effect.

**Ingestion** May be fatal if swallowed and enters airways.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

**Information on toxicological effects**

**Acute toxicity** May be fatal if swallowed and enters airways.

Chemical Name	Dermal LD50	Oral LD50	Inhalation LC50/LD50
Titanium Dioxide 13463-67-7	>10000 mg/kg (Rabbit)	>20000 mg/kg (Rat)	>6.82 mg/l, 4 hours (Rat)
n-Butane 106-97-8	-	-	658 mg/l, 4 hours (Rat)
Methyl Isobutyl Ketone 108-10-1	16000 mg/kg (Rabbit)	2100 mg/kg (Rat)	8.3-16.6 mg/l, 4 hours (Rat)
Isobutyl Acetate 110-19-0	222mg/kg (Mouse)	4763 mg/kg (Rat)	-
Xylene 1330-20-7	2000 mg/kg (Rabbit)	8700 mg/kg (Rat)	6350 mg/l, 4 hours (Rat)

\*Estimates for product may be based on additional component data not shown.

**Skin/Eye irritation** No irritant to skin. Irritating effect for eyes.

**Sensitization** This product is not expected to be hazardous.

**Germ cell mutagenicity** No information available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is considered to be a carcinogen by IARC. Titanium Dioxide (13463-67-7)2B – Methyl Isobutyl ketone (108-10-1)2B – Xylene (1330-20-7)3. This product is not considered to be a carcinogen by NTP, ACGIH or OSHA.

**STOT - single exposure** No Information available.

**STOT - repeated exposure** No Information available.

**Target organ effects** No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**  
Hazardous for water, do not empty into drains.

**Persistence and degradability**  
This product is degradable after prolonged exposure to natural weathering processes

**Bioaccumulation**  
No Information available.

**Mobility in Soil**  
No information available.

**Other adverse effects** No other adverse environmental effects.

**13. DISPOSAL CONSIDERATIONS**

<b>Disposal of wastes</b>	Dispose of in accordance with local, state, and federal regulations. Do no puncture, incinerate or crush. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Completely empty cans should be recycled.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.

**14. TRANSPORT INFORMATION**

This product meets the exception requirements of Section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the “Consumer Commodity-ORM-D” marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/2020 and may be used now in place of the “Consumer Commodity ORM-D” marking and both may be displayed concurrently.

**DOT**

<b>UN/ID No.</b>	UN1950
<b>Proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	2.1

**IATA**

<b>UN/ID No.</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	2.1
<b>Excepted quantities</b>	Code: E0 – Not permitted as Excepted Quantity
<b>Quantity limitations</b>	On passenger aircraft/rail: 75kg On cargo aircraft only: 150 kg

**IMDG**

<b>UN/ID No.</b>	UN1950
<b>Proper shipping name</b>	Aerosols, flammable
<b>Limited quantities (LQ)</b>	1L
<b>Expected quantities</b>	Code: E0 – Not permitted as Excepted Quantity
<b>Marine Pollutant</b>	No
<b>Special precautions for user</b>	Warning: Gases
<b>EMS Number</b>	F-D, S-U

**15. REGULATORY INFORMATION**

**International Inventories**

**Country(s) or Region**

Canada	Yes*
Puerto Rico	Yes*

\*Yes indicates this product complies with the inventory requirements administered by the governing country(s).

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations**

**SARA 313 (Specific toxic chemical listings):** Methyl Isobutyl Ketone (108-10-1), Barium Sulfate, natural (7727-43-7), Xylene – Mix (1330-20-7)

**Superfund Amendments and Reauthorization Act of 1986**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	Yes

**US State Regulations**

**Canadian Environmental Protection Act**

Acetone (67-64-1) , Methyl Isobutyl Ketone (108-10-1), Barium Sulfate, natural (7727-43-7), Isobutyl Acetate (110-19-0), Xylene, mix (1330-20-7)

**Consumer Product Safety Commission**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Titanium Dioxide (13463-67-7), Methyl Isobutyl Ketone (108-10-1), Ethyl Benzene (100-41-4)

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	Health hazards -	Flammability -	Reactivity -	Physical and Chemical Properties -
<b><u>HMIS</u></b>	Health hazards 1	Flammability 4	Reactivity 3	Personal protection X

Issue Date	11-Apr-2015
Revision Date	24-July-2015
Revision Note	

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**



## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product identifier**

**Product Name** United 154 HIGH-COAT Matte Grey

**Other means of identification**

**SDS#** UNITED-154MG

**Recommended use of the chemical**

**And restrictions on use**

**Recommended use** Industrial Strength Spray Paint Matte Grey  
**Uses Advised Against** For industrial and institutional use only.

**Details of the supplier of the safety data sheet**

**Company Name**

United Laboratories, Inc.  
 320 37th Avenue  
 St. Charles, IL 60174  
 www.unitedlabsinc.com  
 www.unitedlabsinc.ca

**Emergency telephone number**

**Emergency Telephone** 800-323-2594 (to reorder)  
 INFOTRAC 1-800-535-5053 (North America)  
 1-352-323-3500 (International)

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable Aerosols	Category 1
Pressurized Gas	
Eye Irritation	Category 2A
Carcinogenicity	Category 2
STOT – Single Exposure	Category 2
STOT – Repeated Exposure	Category 3

**Label elements**

**Emergency Overview**

# Danger

**Hazard statements**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of causing cancer. May cause respirator irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. If medical advice is needed, have product container or label at hand.

**Appearance** Matte Grey Liquid**Physical state** Aerosol**Odor** Aromatic**Prevention**

Read label before use. If medical advice is needed, have product container or label at hand. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Wash hands thoroughly after handling. Keep out of reach of children. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray.

**Response**

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

**Storage**

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in well-ventilated area. Keep container tightly closed.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

Not classified.

**Environmental hazards**

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	18.03%	*
Propane	74-98-6	15.82%	*
n-Butane	106-97-8	9.29%	*
Calcium Carbonate	1317-65-3	8.18%	*
Titanium dioxide	13463-67-7	6.89%	*
Methyl Isobutyl Ketone	108-10-1	5.03%	*
Glycol Ether EP	2807-30-6	4.87%	*
Isobutyl Acetate	110-19-0	3.49%	*
Methyl Propyl Ketone	107-87-9	2.67%	*
Xylene (Mix)	1330-20-7	2.43%	*
PM acetate	108-65-6	1.7%	

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**First aid measures****Skin Contact**

Remove contaminated clothing. Wash exposed area with soap and water.

**Eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**Inhalation** Supply fresh air; consult doctor in case of complaints.

**Ingestion** Rinse mouth water and drink plenty of water. Do not induce vomiting.

**Most important symptoms and effects, both acute and delayed**

May cause dizziness.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Extinguishing powder or water spray. CO2.

**Unsuitable extinguishing media** None known.

**Specific hazards arising from the chemical**

Can form explosive gas-air mixtures.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure demand, MSHA/NIOSH (approved or equivalent) and full protective gear. A respiratory protective device may be necessary.

**Specific Methods**

Use water spray to fight larger fires. Ventilate area.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Keep unnecessary personnel away. Wear appropriate protective equipment. Use respiratory protective device against the effects of fumes/dust/aerosol. For personal protection, see Section 8 of this SDS.

**Environmental precautions**

**Environmental precautions** Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage into sewer systems or ground water. Eliminate all ignition sources (no smoking, flares, sparks or flames).

**Methods for cleaning up** Prevent entry into waterways, sewers. Clean contaminated surface thoroughly to remove residual contamination.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Keep away from heat, sparks, flame and other sources of ignition, and direct sunlight. Use in well ventilated areas. Keep away from children.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store locked up. Do not handle or store near flame, heat and sources of ignition. Avoid exposure to direct sunlight, exceeding 50°C/122°F. Do not warehouse in subfreezing conditions.

**Incompatible materials** None known.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines** No Exposure limits noted for ingredient(s).

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	TWA: 500 ppm	PEL: 2400 mg/m <sup>3</sup> PEL: 1000 ppm	TWA: 590 mg/m <sup>3</sup> TWA: 250 ppm
Propane 74-98-6	Refer to Appendix F	PEL: 1800 mg/m <sup>3</sup> PEL: 1000 ppm	TWA: 1800 mg/m <sup>3</sup> TWA: 1000 ppm
n-Butane 106-97-8	TWA: 2370 mg/m <sup>3</sup> TWA: 1000 ppm	-	TWA: 1900 mg/m <sup>3</sup> TWA: 800 ppm
Methyl Isobutyl Ketone 108-10-1	TWA: 307 mg/m <sup>3</sup> TWA: 75 ppm TWA: 82 mg/m <sup>3</sup> TWA: 20 ppm	PEL: 410 mg/m <sup>3</sup> PEL: 100 ppm	TWA: 300 mg/m <sup>3</sup> TWA: 75 ppm TWA: 205 mg/m <sup>3</sup> TWA: 50 ppm
Xylene 1330-20-7	TWA: 651 mg/m <sup>3</sup> TWA: 150 ppm TWA: 434 mg/m <sup>3</sup> TWA: 100 ppm	PEL: 435 mg/m <sup>3</sup> PEL: 100 ppm	TWA: 655 mg/m <sup>3</sup> TWA: 150 ppm TWA: 435 mg/m <sup>3</sup> TWA: 100 ppm
Methyl Propyl Ketone 107-87-9	TWA: 529 mg/m <sup>3</sup> TWA: 150 ppm	PEL: 700 mg/m <sup>3</sup> PEL: 200 ppm	TWA: 530 mg/m <sup>3</sup> TWA 150 ppm
PM Acetate 108-65-6	WEEL: 50 ppm	-	-
Isobutyl Acetate 110-19-0	TWA: 713 mg/m <sup>3</sup> TWA: 150 ppm	PEL 700 mg/m <sup>3</sup> PEL: 150 ppm	TWA: 700 mg/m <sup>3</sup> TWA: 150 ppm

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Biological limit values** Acetone (67-64-1) - 50 mg/L – Urine / Methyl Isobutyl Ketone (108-10-1) – 1mg/L – Urine  
Xylene (1330-20-7) – 1.5 g/g creatinine - Urine

**Appropriate engineering controls**

**Engineering Controls** Local exhaust is recommended.

**Individual protection measures, such as personal protective equipment**

- Eye/face protection** Tightly sealed goggles.
- Skin and body protection** Protective gloves. The glove material must be impermeable and resistant to the substance.
- Respiratory protection** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**General Hygiene** Keep away from foodstuffs and animal feed. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	Aerosol
<b>Appearance</b>	Spray
<b>Color</b>	Matte Grey
<b>Odor</b>	Aromatic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No Information available.	
Specific Gravity	0.77-0.85 (H2O=1)	
Viscosity	No Information available.	
Melting point/freezing point	-44° C (-47°F)	
Flash point	-19 °C (-2°F)	
Vapor pressure	No information available.	
Vapor density	No Information available	
Flammability (solid, gas)	In use, may form flammable/explosive vapor-air mixture.	
Upper Explosion Limit	10.9 vol.%	
Lower Explosion Limit	1.7 vol.%	
Auto-Ignition	Is not self-igniting	
VOC Content	494.6 g/l/ 4.13lb/gl	
VOC Content (less exempt solvents)	46.6%	
MIR Value	1.05	
Relative density	Between 0.77 and 0.85 (water equals 1.00)	
Vapor density	No information available.	
Solubility	Insoluble	
Solids content	35%	

## 10. STABILITY AND REACTIVITY

### Reactivity

This product is stable and non-reactive under normal conditions of use, storage and transport.

### Chemical stability

Material is stable at normal conditions.

### Possibility of Hazardous Reactions

No dangerous reactions known.

### Conditions to avoid

Do not allow can to exceed 120° F. Do not warehouse in subfreezing temperatures.

### Hazardous Decomposition Products

No hazardous decomposition products are known.

### Incompatible materials

No information available.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	May be fatal if swallowed and enters airways.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Skin Contact</b>	No irritating effect.

**Ingestion** May be fatal if swallowed and enters airways.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

**Information on toxicological effects**

**Acute toxicity** May be fatal if swallowed and enters airways.

Chemical Name	Dermal LD50	Oral LD50	Inhalation LC50*/LD50
Titanium Dioxide 13463-67-7	>10000 mg/kg (Rabbit)	>20000 mg/kg (Rat)	>6.82 mg/l, 4 hours (Rat)
n-Butane 106-97-8	-	-	658 mg/l, 4 hours (Rat)
Methyl Isobutyl Ketone 108-10-1	16000 mg/kg (Rabbit)	2100 mg/kg (Rat)	8.3-16.6 mg/l, 4 hours (Rat)
Isobutyl Acetate 110-19-0	-	4763 mg/kg (Rat)	-
PM Acetate 108-65-6	-	8500 mg/kg (Rat)	35.7 mg/l * (Rat)
Xylene 1330-20-7	2000 mg/kg (Rabbit)	8700 mg/kg (Rat)	6350 mg/l, 4 hours (Rat)

\*Estimates for product may be based on additional component data not shown.

**Skin/Eye irritation** No irritant to skin. Irritating effect for eyes.

**Sensitization** This product is not expected to be hazardous.

**Germ cell mutagenicity** No information available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is considered to be a carcinogen by IARC. Titanium Dioxide (13463-67-7)2B – Methyl Isobutyl ketone (108-10-1)2B – Xylene (1330-20-7)3. This product is not considered to be a carcinogen by NTP, ACGIH or OSHA.

**STOT - single exposure** No Information available.

**STOT - repeated exposure** No Information available.

**Target organ effects** No information available.

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**  
Hazardous for water, do not empty into drains.

**Persistence and degradability**  
This product is degradable after prolonged exposure to natural weathering processes

**Bioaccumulation**  
No Information available.

**Mobility in Soil**  
No information available.

**Other adverse effects**  
No other adverse environmental effects.

**13. DISPOSAL CONSIDERATIONS**

**Disposal of wastes** Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate or crush. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Completely empty cans should be recycled.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**14. TRANSPORT INFORMATION**

This product meets the exception requirements of Section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity-ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/2020 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**DOT**

**UN/ID No.** UN1950  
**Proper shipping name** Aerosols, flammable  
**Transport hazard class(es)** 2.1

**IATA**

**UN/ID No.** UN1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)** 2.1  
**Excepted quantities** Code: E0 – Not permitted as Excepted Quantity  
**Quantity limitations** On passenger aircraft/rail: 75kg  
 On cargo aircraft only: 150 kg

**IMDG**

**UN/ID No.** UN1950  
**Proper shipping name** Aerosols, flammable  
**Limited quantities (LQ)** 1L  
**Expected quantities** Code: E0 – Not permitted as Excepted Quantity  
**Marine Pollutant** No  
**Special precautions for user** Warning: Gases  
**EMS Number** F-D, S-U

**15. REGULATORY INFORMATION**

**International Inventories**

**Country(s) or Region**

Canada Yes\*  
 Puerto Rico Yes\*

\*Yes indicates this product complies with the inventory requirements administered by the governing country(s).

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations**

**SARA 313 (Specific toxic chemical listings):** Methyl Isobutyl Ketone (108-10-1), Xylene (Mix) (1330-20-7)

**Superfund Amendments and Reauthorization Act of 1986**

**Acute health hazard** Yes  
**Chronic Health Hazard** No  
**Fire hazard** Yes

Sudden release of pressure hazard Yes

**SARA 355 (Extremely hazardous substance)**

None known.

**US State Regulations**

**Canadian Environmental Protection Act**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

**EPA**

Acetone (67-64-1), Methyl Isobutyl Ketone (108-10-1), Isobutyl Acetate (110-19-0), Xylene, mix (1330-20-7).

**Consumer Product Safety Commission**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**USDA (United States Department of Agriculture)**

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact.

**California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Titanium Dioxide (13463-67-7), Methyl Isobutyl Ketone (108-10-1), Ethyl Benzene (100-41-4), Carbon black

**16. OTHER INFORMATION**

<b><u>NFPA</u></b>	<b>Health hazards -</b>	<b>Flammability -</b>	<b>Reactivity -</b>	<b>Physical and Chemical Properties -</b>
<b><u>HMIS</u></b>	<b>Health hazards 1</b>	<b>Flammability 4</b>	<b>Reactivity 3</b>	<b>Personal protection X</b>

Issue Date 11-Apr-2015  
 Revision Date 06-August-2015  
 Revision Note

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**